

# Chenbro SR102 (Echo)

[www.chenbro.com.tw/](http://www.chenbro.com.tw/)



## Additional Information

Associated Model #s:

Options: Hot Swap Drives.  
Redundant PSU

Chassis Configuration (Server Board SAI2 Tested Chassis List Based On Mechanical and Thermal Regression Testing of Chassis Posted on Server Board STL2 Reference List)

Model tested: SR102 (Echo)

Fans (qty x size): 5 x 90 mm

Hard drives: 3 x Seagate\* ST328451 LW Cheetah\*

Processor: 2 x 1 GHz Pentium® III FC-PGA

Memory: 256 MB SDRAM

Power Supply: EMACS AP2-5400F-RV2

RAID: Intel, BOXSRCU31L

Additional Information:

\* Third party names and brands are the property of their respective owners.

Note: Modifications to the tested configuration may cause variations in actual performance.

## Product Information

Model#: SR102 (Echo)

Size (LxWxH in/mm): 22.8x14.8x22.8in/583x376x580mm

5.25" Bays: 11

3.50" Bays: 2 exposed, 4 internal

Fans: 3 x 9cm (9 x 9 cm, 1 x 8 cm, 1 x 6 cm optional)

Power Supply: Dual or Trio Redundant PSU  
3 x PS/2 standard PSU

Other Information: SCA HDD Raid module is optional

Note: The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any inaccuracies in this data or any changes made by the manufacturer.

## List of Intel

### Real Server Boxed Boards

Mechanically Compatible with:

**STL2, SAI2**

Thermally Compatible with:

**STL2, SAI2**

CE Testing Performed with: