

Chenbro SR104 (Genie)

www.chenbro.com.tw/

Additional Information

Associated Model #s:

Options: PS/2 Redundant PSU

<u>Chassis Configuration</u>: (Server Board SAI2 Tested Chassis List Based On Mechanical and Thermal Regression Testing of Chassis

Posted on Server Board STL2 Reference List)

Model tested: SR104 (Genie)

Fans (qty x size): 2 x 120 mm, 1 x 90 mm

Hard drives: 3 x Seagate* ST328451 LW Cheetah* Processor: 2 x 1 GHz Pentium® III FC-PGA

Memory: 256 MB

Power Supply: (Contact Chassis Supplier for information on

Compatible Power Supplies for Server Board SDS2)

RAID: Intel, BOXSRCU31L Additional Information:

* Third party names and brands are the property of their respective owners.

Note: Modifications to the tested configuration may cause

variations in actual performance.

Product Information

Model#: SR104 (Genie)

Size (LxWxH in/mm):18.3x8.89x21.29in/575x226x547mm

5.25" Bays: 4

3.50" Bays: 2 exposed, 5 internal Fans: 2 x 9cm (2 x 12 cm optional) Power Supply: Dual Redundant PSU

PS/2 standard PSU

Other Information: SCA HDD Raid module is optional, Chassis intrusion switch is included

Note: The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any inaccuracies in this data or any changes made by the manufacturer.

List of Intel

Real Server Boxed Boards

Mechanically Compatible with:

STL2, SAI2, SDS2

Thermally Compatible with:

STL2, SAI2, SDS2

CE Testing Performed with: