

Product Information

Model#: EN-8950

Size (LxWxH in/mm): 8.7 x 16.9 x 23.7"/220 X 429 x 600mm

5.25" Bays: 9 3.50" Bays: 1 Fans: 2 x 8cm

Power Supply: Delta RPS-800A (400W)

Other Information: Rack mountable

Note: The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any inaccuracies in this data or any changes made

by the manufacturer.

Additional Information

Associated Model #s: None

Options: Hot swap drives (5 x 1" EN-8700), rack mount

Enlight Corporation EN-8950

www.enlightcorp.com

<u>Chassis Configuration</u>: (Server Board SDS2 Tested Chassis List Based On Mechanical and Thermal Regression Testing of Chassis Posted on Server Board STL2 Reference List) Model tested: EN-

8950

Fans (size, gty): 2 x 80mm, (1 attached to H/S backplane), 1 x

90mm

Hard Drives: 3 x Seagate* ST328451 LC Processor: 2 x 1 GHz Pentium® III FC-PGA

Memory: 256 MB

Power Supply: (Contact Chassis Supplier for information on

Compatible Power Supplies for Server Board SDS2)

RAID: Intel, BOXSRCU31L

Additional Information: Configuration of hard drives were loaded

in the center of the hot swap bay.

* Third Party names and brands are the property of the respective owner.

Note: Modifications to the tested configuration may cause

variations in actual performance.

List of Intel

Real Server Boxed Boards

Mechanical ly Compatible with:

STL2, SAI2, SDS2

Thermally Compatible with:

STL2, SAI2, SDS2

CE Testing Performed with: