

Product Information

Model#: RS 2100

Size (LxWxH in/mm): 24X17X3.468 in / 610x432x88 mm

5.25" Bays: 1

3.50" Bays: 5 (includes 4X Hot Swap SCSI Ultra 3 drive

bays)

Fans: 4 x 80mm (2 x 80mm standard & 2 x 80mm

optional)

Power Supply: CI Design, CA-300ATX

Other Information:

Note: The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any inaccuracies in this data or any changes made by the manufacturer.

Additional Information

Associated Model #s: N/A

Options: Fans, hot swap redundant power supply, Color (Black or Platinum), IDE HDD Removable Tray, Rack Mount Slide Rail Kit, 3PCI Back Panel

Ci Design RS 2100 Rack Server Enclosure www.cidesign.com

<u>Chassis Configuration</u> (as tested with Intel's Server Board

STL2)

Model tested: RS 2100

Fans (qty/size): 4 x 80mm (2 x Standard, 2 x Optional)

Hard drives: 3-Seagate* ST328451LC Cheetah*

Processor: 2 x 1 GHz Pentium® III FC-PGA processor

Memory: 256 MB

Power Supply: CI Design CA-300ATX

RAID: Intel, BOXSRCU31L

Additional Information: Tested With optional fans.

* Third Party names and brands are the property of the respective owner.

Note: Modifications to the tested configuration may cause variations in actual performance.

List of Intel

Real Server Boxed Boards

Mechanically Compatible with:

L440GX+ (850 MHz), STL2

Thermally Compatible with:

L440GX+ (850 MHz), STL2

CE Testing Performed with: