

## www.aicipc.com

## **Product Information**

Model# RMC2R

Size (LxWxH inches/mm) 25.3x19x3.5 / 643x483x89

5.25" Bays: 2

3.50" Bays: 4 internal HDD's

Fans: 3 x 80mm

Power Supply: Emac AX5300 300W ATX

Other Information: 3x32-bit PCI or 2x64-bit PCI offset riser cards, 3xSCA H/S modules (using 2x5.25" bays), and slim CD-ROM + FDD (using 1x5.25") mounting bracket Are available for this chassis.

Note: The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any changes.

## Advanced Industrial Computer RMC2R

Chassis Configuration (as tested with Intel's Server Board

STL2)

Model tested: RMC2R Fans (size, qty): 80mm - 3 Hard drives: 3 Seagate ST318451 LC Processor: 2 - Intel® Pentium III (FC-PGA) Memory: 256 MB Power Supply: EMACS 300W P2U-6300P RAID: Intel, BOXSTCU31L Additional Information:

Note: Modifications to the tested configuration may cause variations in actual performance.

## List of Intel

**Real Server Boxed Boards** 

**Mechanical Validation** 

STL2

**Thermal Validation** 

STL2 EMI (CISPR) Validation

STL2